



Galaxias series

The cloth-like & extremely easy video display solution for Events



Hanging installation only!

The vertical combination by locks,side by locks and magnets



Achieve true bend in all direction

Super easy and fast installation

Big size panel,magnet positioning and light weight(ave.11kg/sq.m),

all make operation simple and time-saving

Model	G3	G4	G6	G7	G9	G12
Pixel pitch	3.91mm	4.68mm	6.25mm	7.81mm	9.37mm	12.5mm
LED lamp	SMD2020	SMD2020/2727	SMD2727	SMD2727	SMD2727	SMD2727
Operating environment	indoor		indoor/semi-outdoor			
Module size(mm)	L125 x W125	L150 x W150	L200 x W100	L125 x W125	L150 x W150	L100 x W200
Panel size(mm)	L500 x W1500 x T70	L600 x W1800 x T70	L800 x W2400 x T70	L750 x W2500 x T70	L600 x W2400 x T70	L600 x W2400 x T70
Weight(kg/sq.m)	11.5	11.5	11.8	12	11.5	9.8
Ideal curvature(°/m)	25~30					
Viewing angle(°)	120					
Pixel density(dot/sq.m)	65,536	45,512	25,600	16,384	11,378	6,400
Scan mode	1/16	1/16	1/16	1/8	1/8	1/8
Brightness(cd/sq.m)	1000	1000/3600	2500	3000	2400	1500
Refresh rate(Hz)	3840	3840	3840	3840	3840	3840
Gray scale(bit)	15/17					
Contrast	5000:1	4000:1				
Protection level	IP40	IP40/IP44	IP40/IP44	IP40/IP44	IP40/IP54	IP40/IP54
Power consumption(W/sq.m)	500/170(Max./Ave.)	500/170(Max./Ave.)	400/150(Max./Ave.)	400/150(Max./Ave.)	330/110(Max./Ave.)	200/70(Max./Ave.)
Power input	100~240VAC/50~60Hz					
Operating temp./humidity(°C/RH)	-40~+60/10~90%					
Maintenance	Rear					

